

## FTTH Fiber Optic Wall Outlets Terminal Box

### Description

TKS-1806-04D is a desk mounted or wall mounted termination box for end user, indoor use, capable to handle fiber fusion, fiber cables and pigtails.

### Application

- FTTH
- Local area network (LAN)
- Radio and television network (CATV)


### Features

- ◆ Support termination, splicing and storage for fiber optic cable systems
- ◆ Compatible with G.657
- ◆ Compact structure and perfect fiber management
- ◆ Engineered fiber routing protect bend radius through the unit to ensure signal integrity



Model No.:TKS-1806-04D

### Parameter

Parameter	FTTH Fiber Optic Wall Outlets Terminal Box	
Model No.	TKS-1806-04D	
Outside Dimension (mm)	100*83*29 mm	
Material	ABS	
Color	White	
Splice Method	Fusion Splice (45mm sleeve)	
Adapter count	4*SC	4*LC
Adaptor type	Simplex	Duplex
Output	4fiber	8fiber
Application	3.0x2.0mm drop cable or 2.0-6.0mm circular cable	
Fiber diameter	125μm	
Tight cladding diameter	250μm & 900μm	
Insertion loss	≤0.3dB	
Mode of application	Single-mode	
Tensile strength	>50 N	
End-use temperature	-40~+85℃	
Accessories		
No.	Type	
1	Fiber splice protection sleeve	
2	Expansion bolts for the outlet wall-mounted	